

071
rtc TYPE

TYPE 071

Female thread socket / Kuplung mit Innengewinde



Socket / Kuplung	Size / Größe	Order No / Bestellnr.	Ød	Ød1	L	HEX.
	06	071.06 SFB 13	BSP 1/4	30	50	23
		071.06 SNB 13	NPT 1/4	30	50	23
	09	071.09 SFB 17	BSP 3/8	40	60	30
		071.09 SNB 17	NPT 3/8	40	60	30
	13	071.13 SFB 21	BSP 1/2	48	70	38
		071.13 SNB 21	NPT 1/2	48	70	38
	19	071.19 SFB 26	BSP 3/4	57	77.5	44
		071.19 SNB 26	NPT 3/4	57	77.5	44
	25	071.25 SFB 33	BSP 1	67	84.5	50
		071.25 SNB 33	NPT 1	67	84.5	50
	30	071.30 SFB 42	BSP 1-1/4	67	93	50
		071.30 SNB 42	NPT 1-1/4	67	93	50

TYPE 071

Female thread socket / Kuplung mit Innengewinde



Socket / Kuplung	Size / Größe	Order No / Bestellnr.	Ød	Ød1	L	HEX.
	06	071.06 PFB 13	BSP 1/4	30	50	23
		071.06 PNB 13	NPT 1/4	30	50	23
	09	071.09 PFB 17	BSP 3/8	40	60	30
		071.09 PNB 17	NPT 3/8	40	60	30
	13	071.13 PFB 21	BSP 1/2	48	70	38
		071.13 PNB 21	NPT 1/2	48	70	38
	19	071.19 PFB 26	BSP 3/4	57	77.5	44
		071.19 PNB 26	NPT 3/4	57	77.5	44
	25	071.25 PFB 33	BSP 1	67	84.5	50
		071.25 PNB 33	NPT 1	67	84.5	50
	30	071.30 PFB 42	BSP 1-1/4	67	93	50
		071.30 PNB 42	NPT 1-1/4	67	93	50

TYPE 071

Technical Specifications



Working Pressure / Betriebsdruck							
Body Size / Größe		High Pressure Stainless Steel Hochdruck Edelstahl		Steel nickel plated Stahl Nickel beschichtet		Standard Stainless steel Standard Edelstahl	
		Bar	PSI	Bar	PSI	Bar	PSI
071.06	1/4	690	10.000	690	10.000	345	5.000
071.09	3/8	690	10.000	690	10.000	345	5.000
071.13	1/2	690	10.000	690	10.000	345	5.000
071.19	3/4	515	7.500	515	7.500	345	5.000
071.25	1	515	7.500	515	7.500	275	4.000
071.30	1-1/4	515	7.500	515	7.500	275	4.000